

TEMPO F 650 PRO



10601200 black

10601201 white

10601202 silver



COMPATIBLE LAMPS

Model	Lamp Type	Power	Voltage	Temp	Life
M38	GY9.5	300W	230V/240V	2950K	2000 hrs
M40	GY9.5	500W	230V/240V	2950K	2000 hrs
T18	GY9.5	500W	230V/240V	3000K	360 hrs
T25	GY9.5	500W	230V/240V	3000K	360 hrs
T26	GY9.5	650W	230V/240V	3050K	600 hrs
T27	GY9.5	650W	230V/240V	3050K	600 hrs

LDR recommends Philips lamps

ACCESSORIES

20100103	colour frame, black
20100103B	colour frame, white
20100103C	colour frame, silver
20100303	4-leaf barndoor, black
20100303B	4-leaf barndoor, white
20100303C	4-leaf barndoor, silver
20100303D	4-leaf barndoor, white/black
20100303E	4-leaf barndoor, silver/black
20100900	hook clamp
20101300	safety bond
20106013	colour scroller Xpress 13
20600003	plate 150x150mm for Xpress13

PRODUCT SPECS

lens type
120mm dia. Fresnel

reflector
55mm dia. glass

microswitch
double-pole

colour frame
150x150mm

throw
2-10m

beam angle
7°-60°

weight
4 kg

Pro-version of the extremely popular Tempo f650 Plus, featuring a double-microswitch disconnecter for safe lamp replacement.

Tempo f650 Pro is a quality yet budget-priced 500W or 650W Fresnel spotlight. It features a slide-focus variable-spread, soft-edged beam which makes it ideal for small, intimate stage areas. Also included as standard are a DIN standard colour frame, safety guard and 1,5m mains cable.

Versione Pro dell'estremamente popolare Tempo f650 Plus, fornita di doppio microinterruttore di sicurezza.

Tempo f650 Pro è un illuminatore fresnel da 500 /650W di elevato livello qualitativo e tuttavia di gamma economica.

Produce un fascio di luce regolabile molto morbido e soffuso, che lo rende ideale per l'utilizzo in scene molto intime e di piccole dimensioni. Fornito di serie completo di telaio portagelatina, rete di protezione e 1,5m cavo di alimentazione.

PHOTOMETRIC DATA T27

SPOT	m Ø	0,2	0,4	0,5	0,6	0,7	0,9	1,0	1,1	1,2
	lux	16.600	7.378	4.150	2.656	1.844	1.355	1.038	820	664
	m	2	3	4	5	6	7	8	9	10
FLOOD	m Ø	2,3	3,5	4,6	5,8	6,9	8,1	9,2	10,4	11,5
	lux	3.096	1376	774	495	344	253	194	153	124
	m	2	3	4	5	6	7	8	9	10

