

12901000 230V black
13901000 120V black



COMPATIBLE LAMPS

CP55	G22	2000W	230V/240V	3200K	480 hrs
CP75	G22	2000W	230V/240V	3200K	480 hrs
CP92	G22	2000W	230V/240V	3200K	400 hrs
CP72	GY16	2000W	230V/240V	3200K	480 hrs
CP91	G22	2500W	230V/240V	3200K	400 hrs
CYX	G38	2000W	120V	3200K	350 hrs

LDR recommends Philips lamps

ACCESSORIES

20100107	colour frame, black
20100307	4-leaf barndoor, black
20101104	alu-grip clamp for BS spigot
20101300	safety bond

PRODUCT SPECS

lens type
200mm dia. Fresnel

reflector
87,5mm dia. glass

microswitch
double-pole

colour frame
245x245mm

throw
3-20 m

beam angle
10°-70°

lamp base
G22 (230V) - G38 (120V)

weight
10,4 kg (230V) - 11,5 kg (120V)

Compact, lightweight and powerful 2/2.5KW fresnel spotlight. It's ideal for all those applications in larger venues where the luminaires are difficult to access and whose position needs to be changed frequently.

A colour frame, safetyguard and 1,5m mains cable are included as standard.

Illuminatore fresnel da 2/2500W estremamente compatto, leggero e potente, dotato di forcina per comando a palo della posizione orizzontale e verticale.

Ideale per tutte quelle installazioni con illuminatori di difficile accesso e la cui posizione debba essere modificata di frequente. Fornito di serie completo di telaio porta-gelatina, rete di protezione e 1,5m cavo di alimentazione.

On request also available with GY16 lamp-base(230V only).

Su richiesta disponibile anche con porta-lampada GY16 (solo 230V).

PHOTOMETRIC DATA CP75

	m Ø	2,3	2,5	2,7	2,9	3,1	3,3	3,5	3,7	3,9
SPOT	lux	1.563	1.331	1.148	1.000	879	779	694	623	563
	m	12	13	14	15	16	17	18	19	20
FLOOD	m Ø	4,2	5,6	7,0	8,4	9,8	11,2	12,6	14,0	15,4
	lux	2.200	1.238	792	550	404	309	244	198	164
	m	3	4	5	6	7	8	9	10	11

