


12806050 black
 12806051 white
 12806052 silver



COMPATIBLE LAMPS

P2/10	R7s	625W	230V/240V	3200K	150 hrs
P2/7	R7s	1000W	230V/240V	3200K	200 hrs
P2/12	R7s	1250W	230V/240V	3200K	200 hrs

LDR recommends Philips lamps



ACCESSORIES

20100112	colour frame, black
20100112B	colour frame, white
20100112C	colour frame, silver
20101412	spare clear safety glass
20100492	4-leaf barndoor, black
20100492B	4-leaf barndoor, white
20100492	4-leaf barndoor, silver
20101104	alu-grip clamp for BS spigot
20101300	safety bond

PRODUCT SPECS

reflector	aluminium, asymmetrical
microswitch	double-pole
colour frame	290x270mm
throw	2-10m
weight	7kg

Asymmetric 1Kw floodlight featuring a pole-operated stirrup for the control of pan and tilt. Ideal to evenly illuminate a backcloth, cyclorama or scenic pieces from an oblique angle in larger venues or TV studios. A colour frame, safety glass and 1,5m mains cable are also included for each unit.

Diffusore asimmetrico da 1000W dotato di forcina per comando a palo. Ideale per l'illuminazione omogenea di fondali e parti di scena, anche da angolazioni oblique, in teatri o studi televisivi.

Fornito di serie di telaio porta-gelatina, vetro di protezione e 1,5m cavo di alimentazione.

Available to special order with extended front chassis for longer gel life.

Su richiesta disponibile anche con telaio anteriore esteso per gelatine dai colori saturi.

PHOTOMETRIC DATA P2/7

HORIZONTAL	PHOTOMETRIC DATA P2/7									
	m Ø	4,8	7,2	9,5	11,9	14,3	16,7	19,1	21,5	23,8
lux	4.688	2.083	1.172	750	521	383	293	231	188	
m	2	3	4	5	6	7	8	9	10	
VERTICAL	PHOTOMETRIC DATA P2/7									
	m Ø	5,7	8,6	11,4	14,3	17,1	20,0	22,9	25,7	28,6
lux	4.950	2.200	1.238	792	550	404	309	244	198	
m	2	3	4	5	6	7	8	9	10	