

12806060 black
 12806061 white
 12806062 silver



COMPATIBLE LAMPS

P2/10	R7s	625W	230V/240V	3200K	150hrs
P2/7	R7s	1000W	230V/240V	3200K	200hrs
P2/12	R7s	1250W	230V/240V	3200K	200hrs

LDR recommends Philips lamps

Symmetric 1Kw floodlight featuring a pole-operated stirrup for the control of pan and tilt. Ideal for applications even in larger venues where a wide, even wash of light for general lighting purposes is needed. A colour frame, safety glass and 1,5m mains cable are also included for each unit.

Diffusore simmetrico da 1000W dotato di forcilla per comando a palo. Ideale all'impiego anche su grandi aree per l'illuminazione generale d'ambiente in installazioni teatrali o in studi televisivi. Fornito di serie di telaio porta-gelatina, vetro di protezione e 1,5m cavo di alimentazione.

Available to special order with extended front chassis for longer gel life.

Su richiesta disponibile anche con telaio anteriore esteso per gelatine dai colori saturi.

ACCESSORIES

20100112	colour frame, black
20100112B	colour frame, white
20100112C	colour frame, silver
20101412	spare clear safety glass
20100492	4-leaf barndoor, black
20100492B	4-leaf barndoor, white
20100492	4-leaf barndoor, silver
20101104	alu-grip clamp for BS spigot
20101300	safety bond

PRODUCT SPECS

reflector	aluminium, symmetrical
microswitch	double-pole
colour frame	290x270mm
throw	2-10m
weight	7kg

PHOTOMETRIC DATA P2/7

HORIZONTAL	PHOTOMETRIC DATA P2/7									
	m Ø	4,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0
lux	4.875	2.167	1.219	750	542	398	305	241	195	
m	2	3	4	5	6	7	8	9	10	
VERTICAL	PHOTOMETRIC DATA P2/7									
	m Ø	4,4	6,5	8,7	10,9	13,1	15,3	17,5	19,6	21,8
	lux	5.125	2.278	1.281	820	569	418	320	253	205
m	2	3	4	5	6	7	8	9	10	

