

SUONO PC 650 PLUS



PC 10602010 black

10602011 white

10602012 silver

PPC 10602110 black

10602111 white

10602112 silver



COMPATIBLE LAMPS

Lamp Type	Wattage	Voltage	Temp. (K)	Life (hrs)
M38	GY9.5 300W	230V/240V	2950K	2000 hrs
M40	GY9.5 500W	230V/240V	2950K	2000 hrs
T18	GY9.5 500W	230V/240V	3000K	360 hrs
T25	GY9.5 500W	230V/240V	3000K	360 hrs
T26	GY9.5 650W	230V/240V	3050K	600 hrs
T27	GY9.5 650W	230V/240V	3050K	600 hrs

LDR recommends Philips lamps

ACCESSORIES

20100103	colour frame, black
20100103B	colour frame, white
20100103C	colour frame, silver
20100303	4-leaf barndoor, black
20100303B	4-leaf barndoor, white
20100303C	4-leaf barndoor, silver
20100303D	4-leaf barndoor, white/black
20100303E	4-leaf barndoor, silver/black
20100900	hook clamp
20101300	safety bond
20106013	colour scroller Xpress 13
20600003	plate 150x150mm for Xpress13

PRODUCT SPECS

lens type
120mm dia. pebble-convex

reflector
55mm dia. glass

microswitch
double-pole

colour frame
150x150mm

throw
2-10m

beam angle
7°-58°

weight
4,4 kg

Quality 500/650W PC spotlight ideal for professional usage in smaller venues. The well-defined beam is adjustable by a screw-focus mechanism, and the design also includes a hinged lamp-tray and a double-microswitch interlock for safe lamp replacement.

A colour frame, safety guard and 1,5m mains cable are all included as standard.

Illuminatore piano-convesso da 500/650W per uso professionale su piccole scene. Produce un fascio di luce molto omogeneo. E' dotato di carrello porta-lampada basculante ad apertura frontale e di doppio microinterruttore di sicurezza.

Fornito di serie completo di telaio portagelatina, rete di protezione e 1,5m cavo di alimentazione.

	m	2	3	4	5	6	7	8	9	10
SPOT	m Ø	0,2	0,4	0,5	0,6	0,7	0,9	1,0	1,1	1,2
	lux	24.800	11.022	6.200	3.968	2.756	2.024	1.550	1.225	992
	m	2	3	4	5	6	7	8	9	10
FLOOD	m Ø	2,2	3,3	4,3	5,5	6,7	7,8	8,9	10,0	11,1
	lux	2.148	955	537	344	239	175	134	106	86
	m	2	3	4	5	6	7	8	9	10

