

# XPRESS 19 DMX/RDM



20106019 black



## OPERATIONAL

### gel string capacity

8-11-16- 21 frames

### gel string movement

continuous/step,  
remotely controlled

### scroll speed

min. 1,9 sec  
(head to tail with 21 frames)

### gel string cooling

single fan; 5 preset variable  
speeds or remotely  
controlled

### motor

2 DC servo motors directly  
fixed to the rollers

### DMX/power in & out

XLR 4-pin male – DMX512  
and 24V DC power

### daisy chaining

6 or 24 units using PDU6  
or PDU24

### DMX channels

1 to 5 DMX addressable  
channels

### operational modes

continuous or step

The Xpress 19, DMX/RDM-controllable colour scroller, is designed for use with all LDR 1/1,2KW luminaires or any with a front aperture up to 195mm.

It features 4 front attachments for an optional rotating barndoor and is supplied with fitted 21-colour Lee filter gel string, a 253x253mm rear mounting plate and black steel safety bond.

Xpress 19, scroller a controllo DMX/ RDM è adatto a tutti gli illuminatori LDR da 1/1,2KW e ad altri illuminatori con apertura frontale fino a 195mm. E' dotato di 4 supporti frontali per il fissaggio di un paraluce 4 alette accessorio e viene fornito completo di stringa di gelatina con 21 colori Lee, piastra di montaggio 253x253mm e cavo di sicurezza nero.

## ACCESSORIES

20600006	rear mounting plate 185x185mm
20100319	4-leaf barndoor, aluminium
20620019	spare gel string 21 frames, Lee filter, standard sequence
20621019	spare gel string 21 frames, Lee filter, special sequence


## ELECTRICAL

### current requirement

0.6 amps (+24 V DC)

### power consumption

12W



## PRODUCT SPECS

### construction

sturdy aluminium

### paint finish

black epoxy powder coating

### rear mounting plate

253x253mm, fitted

### barndoor plate

215x215mm

### safety cable

60cm, steel, included

### weight

2,7kg