

PDU POWER DISTRIBUTION UNIT



The PDU (power distribution unit) distributes DC power (24V) and the DMX data signal through the XLR4- pin female plug to max. 1, 6 or 24 Xpress colour scrollers.

The DMX signal can be daisy-chained from the PDU to any other DMX device. Each PDU is delivered with a hook clamp, CEE22 power cord and steel safety bond.

Il PDU (power distribution unit) distribuisce sia l'alimentazione (24V) sia il segnale di controllo DMX ad un massimo di 1, 6 o 24 Xpress collegati in sequenza.

Il segnale DMX può trasmesso in sequenza dal PDU a qualsiasi apparecchiatura a controllo DMX. Il PDU viene fornito completo di gancio di sospensione, cavo di alimentazione con CEE22 e cavo di sicurezza in acciaio.

PRODUCT SPECS

construction

sturdy aluminium housing

paint finish

black epoxy powder coating

safety cable

60cm black safety cable, supplied

ACCESSORIES


20610003	DMX XLR-4 pin cable 3m
20610005	DMX XLR-4 pin cable 5m
20610010	DMX XLR-4 pin cable 10m
20610015	DMX XLR-4 pin cable 15m
20610020	DMX XLR-4 pin cable 20m
20610025	DMX XLR-4 pin cable 25m

Special-lenght cables are available on request.

PDU 7

20106020 black

Power distribution unit for 1 scroller.



weight
1,3 kg



ELECTRICAL

power input

100V-240V 50/60Hz

power output

24V DC

OPERATIONAL

DMX input to PDU

XLR 5-pin male

DMX / power output

XLR 4-pin-female
DMX 512 + 24V

DMX channels

1 or 2 channels per scroller