

ARIA PC 1000 PLUS



PC 10802000 black	PPC 10802100 black
10802001 white	10802101 white
10802002 silver	10802102 silver



COMPATIBLE LAMPS

CP67	GX9.5	650W	230V/240V	3200K	120 hrs
T21	GX9.5	650W	230V/240V	3000K	900 hrs
CP70	GX9.5	1000W	230V/240V	3200K	240 hrs
T19	GX9.5	1000W	230V/240V	3050K	900 hrs
CP90	GX9.5	1200W	230V/240V	3200K	240 hrs
T29	GX9.5	1200W	230V/240V	3000K	480 hrs

LDR recommends Philips lamps

ACCESSORIES

20100106	colour frame, black
20100106B	colour frame, white
20100106C	colour frame, silver
20100306	4-leaf barndoor, black
20100306B	4-leaf barndoor, white
20100306C	4-leaf barndoor, silver
20100306D	4-leaf barndoor, white/black
20100306E	4-leaf barndoor, silver/black
20100900	hook clamp
20101300	safety bond
20106019	colour scroller Xpress 19
20600006	plate 185x185mm for Xpress 19

PRODUCT SPECS

lens type
150mm dia. pebble-convex

reflector
100mm dia. aluminium

microswitch
no

colour frame
185x185mm

throw
2-17m

beam angle
8°-60°

weight
6 kg

Compact, high-quality yet budget-priced 650W- 1200W PC spotlight producing a variable, well defined beam ranging from 8° to 60°. It is ideal for non professional applications in medium-sized venues. A colour frame, safety guard and 1,5m mains cable are all included as standard.

Illuminatore piano-convesso da 1000/1200W, di elevato standard qualitativo e tuttavia di gamma economica. Produce un fascio di luce dai bordi ben definiti e regolabile tra 8° e 60°.

E' particolarmente indicato in utilizzi non professionali su distanze medio-lunghe. Fornito di serie completo di telaio portagelatina, rete di protezione e 1,5 m cavo di alimentazione.

PHOTOMETRIC DATA CP90

	m Ø	1,0	1,1	1,3	1,4	1,5	1,7	1,8	2,0	2,1
SPOT	lux	4.996	3.825	3.022	2.448	2.032	1.700	1.449	1.249	1.088
	m	7	8	9	10	11	12	13	14	15
	m Ø	2,3	3,5	4,6	5,8	6,9	8,1	9,2	10,4	11,5
FLOOD	lux	2.440	1.084	610	390	271	199	153	120	98
	m	2	3	4	5	6	7	8	9	10

