

Application

Beam style	symmetric flood
Suitable for	small-scale theatre, general floodlighting
Specification level	professional range
Typical throw distance	2 - 5m

Electrical specifications

Supply Volts	230/240V AC single phase
Max. Lamp Watts	500W
Lamp base	R7s
Auto-disconnect	single-pole microswitch
Cable/connection	1.5m, 3 x 1.5mm ² flexible cable to bare ends
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Paint/Finish	black/silver/white epoxy powder paint
Lamp House Construction	1-compartment. A full range of units and accessories for multiple row general floodlighting is available to separate order
Reflector	symmetrical, aluminium
Mounting & suspension	steel stirrup with 12mm centre hole and DIN mounting
Weight/Packed weight	2,6kg / 3,1kg
Packed volume	0.017m ³
Filter cut size	244 x 195mm
Accessory runners	3 slots
Safety glass	supplied
Colour frame	metal, 244 x 195mm supplied
Lamp access	front access

Operational specifications

Working position	max. tilting $\pm 180^\circ$ from vertical
Positional adjustment	tilt lock on one side

Lamp types

160W	Plusline ES Small R7s 230V 3100lm 2.000 hrs
240W	Plusline ES Small R7s 230V 4900lm 2.000 hrs
400W	Plusline ES Small R7s 230V 8700lm 2.000 hrs

Accessories

Spare metal colour frame	■ 20100121 □ 20100121B ■ 20100121C
Clear safety glass	20101420
Safety guard	20100220
4-leaf barndoor	■ 20100420 □ 20100420B ■ 20100420C □ ■ 20100420D ■ 20100420E
Hook clamp	20100900
Safety bond	20101300

For full info on Rima modular system please see **Rima S500 Pro no-stirrup data sheet**

Photometric data

Horizontal	ES400									
Beam dia.	3.2	4.9	6.5	8.1	9.7	11.3	13	14.6	16.2	m
lux	913	406	228	146	101	74	57	45	37	
Distance	2	3	4	5	6	7	8	9	10	m

Vertical										
Beam dia.	1.9	2.9	3.8	4.8	5.7	6.7	7.6	8.6	9.5	m
lux	1345	598	336	215	149	110	84	66	54	
Distance	2	3	4	5	6	7	8	9	10	m


LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

rima[®] S500 F Pro

200 - 500W

symmetric floodlight

part number: ■ 10516060 □ 10516061 ■ 10516062



Stylish and high specification 500W symmetric floodlights, ideal for all applications where a wide, even wash of light is required. Accurate design prevents any light spill.

Rima S500F Pro is designed for usage as single module flood, and is delivered complete with colour frame, a single microswitch interlock for safe lamp replacement, a safety glass and 1.5m mains cable, whereas a large choice of accessories is available as optional extras.

Available to special order with extended front chassis for longer gel life.



Luci della Ribalta srl
Via Berna 14
46042 Castel Goffredo (MN), Italy
tel: +39 0376 771777
fax: +39 0376 772140
www.ldr.it info@ldr.it

issue: ap ©2020. LDR reserves the right to alter the specification without prior notice.