

Application

Beam style	variable-spread, well-defined soft beam
Suitable for	theatre, clubs, small stage areas
Specification level	economy range
Beam angle	7° - 60°
Typical throw distance	2 - 10m

Electrical specifications

Supply Volts	230/240V AC single phase
Max. Lamp Watts	650W
Lamp base	GY9.5
Auto-disconnect	no
Cable/connection	1.5m, 3x1.5mm ² flexible cable to bare ends
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Paint/Finish	black epoxy powder paint
Lamp House Construction	extruded aluminium and sheet steel
Reflector	55mm diameter glass
Lens	120mm diameter Fresnel
Mounting & suspension	steel stirrup with 12mm centre hole and DIN mounting. Stirrup rotates 360° around the body of the luminaire
Rear handle	yes
Weight/Packed weight	4 kg / 4,6kg
Packed volume	0.021m ³
Filter cut size	150 x 150mm
Accessory runners	3 slots
Safety guard	included
Colour frame	metal, 150x150mm, supplied
Lamp access	sliding top cover
Lens access	front and via lamp access

Operational specifications

Focus adjustment	slide focus with control underneath
Working position	max. tilting ±90° from horizontal
Beam Shaping	using barndoor accessory
Positional adjustment	single rim-clamp tilt lock

Lamp types

300W	M38 2950K 2000 hrs
500W	T18 3000K 360 hrs / T25 3000K 360 hrs / M40 2950K 2.000 hrs
650W	T26 3050K 600 hrs / T27 3050K 600 hrs

LDR recommends Philips lamps

Accessories

Spare metal colour frame	■20100103	□20100103B	■20100103C
Spare safety guard	■20100203	□20100203B	■20100203C
4-leaf barndoor	■20100303	□20100303B	■20100303C
	□■20100303D	■20100303E	
Hook clamp	20100900	Alu-grip clamp	20101100
Safety bond	20101200		
Colour scroller Xpress 13	20106013 with mounting plate 20600003		

Photometric data

Spot focus												T27
Beam dia.	0.2	0.4	0.5	0.6	0.7	0.9	1.0	1.1	1.2	m		
lux	16600	7378	4150	2656	1844	1355	1038	820	664			
Distance	2	3	4	5	6	7	8	9	10	m		


Flood focus											
Beam dia.	2.3	3.5	4.6	5.8	6.9	8.1	9.2	10.4	11.5	m	
lux	3096	1376	774	495	344	253	194	153	124		
Distance	2	3	4	5	6	7	8	9	10	m	

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

tempo® f650 plus

650W fresnel


part number : ■10601000 □10601001 ■10601002



Quality yet budget-priced 500W or 650W Fresnel spotlight. It features a slide-focus variable-spread, soft-edged beam which makes it ideal for small, intimate stage areas.

Also included as standard are a DIN standard colour frame, safety guard and 1.5m mains cable.

Available to special order in any colour from the RAL range



Luci della Ribalta srl
Via Berna 14
46042 Castel Goffredo (MN), Italy
tel: +39 0376 771777
fax: +39 0376 772140
www.ldr.it info@ldr.it

issue: ap ©2008. LDR reserves the right to alter the specification without prior notice.