

## Application

Beam style	well-defined, flat field profile projection
Suitable for	large scale theatre
Specification level	professional range
Beam angle	18° - 36°
Typical throw distance	6 – 23m

## Electrical specifications

Supply Volts	230/240V AC single phase
Max. Lamp Watts	2000W
Lamp base	GY16
Auto-disconnect	double-pole microswitch
Cooling	low-noise fan-assisted ventilation
Cable/connection	2m, 3 x 2.5mm <sup>2</sup> flexible cable to bare ends
Standards Compliance	EN60598-2-17, CE marked

## Mechanical specifications

Paint/Finish	black epoxy powder paint
Lamp House Construction	extruded aluminium and sheet steel
Reflector	68mm diameter, aluminium
Optical system	double condenser with variable zoom
Mounting & suspension	steel stirrup with 12mm centre hole and DIN mounting.
Handle	rear
Weight/Packed weight	14 kg / 17kg
Packed volume	0.17m <sup>3</sup>
Filter cut size	185 x 185mm
Accessory runners	3 slots
Safety guard	supplied
Colour frame	metal, 185 x 185mm, supplied
Lamp access	hinged base
Lens access	hinged panel on top of lamp tube

## Operational specifications

Focus adjustment	slide zoom controls (dia/softness) at side
Lamp alignment	factory set
Beam Shaping	4 shutters, included + iris, accessory
Positional adjustment	lever tilt clamp

## Lamp types

2000W	CP72 GY16 230/240V 3200K 480 hrs
-------	----------------------------------

LDR recommends Philips lamps

## Accessories

Lamps	see above
Spare metal colour frame	20100106
Spare safety guard	20100206
Iris diaphragm	20100706
Gobo holder, A/B size, metal	20100806
Hook clamp HD	20101000
Alu-grip clamp	20101100
Safety bond	20101200
Colour scroller Xpress 19	20106019 with mounting plate 20600006

## Photometric data


Narrow focus		CP72									
Beam dia.		2.5	3.2	3.8	4.4	5.1	5.7	6.3	7.0	7.6	m
lux		4328	2770	1924	1413	1082	855	693	572	481	
Distance		8	10	12	14	16	18	20	22	24	m

Wide focus											
Beam dia.		3.9	5.2	6.5	7.8	9.1	10.4	11.7	13.0	14.3	m
lux		5556	3152	2000	1389	1020	781	617	500	413	
Distance		6	8	10	12	14	16	18	20	22	m

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS


# tono<sup>®</sup> 18/36 2000W profile spotlight

part number 10903030



For closer projection in larger venues, this wide-angle 18° - 36° 2000W spotlight incorporates a zoom focus double condenser optical system, rotating gate, a cranked fork and a double microswitch interlock for safe lamp replacement.

A colour frame, safety guard, 4 beam shutters and 2m mains cable are also included.



Luci della Ribalta srl  
Via Berna 14  
46042 Castel Goffredo (MN), Italy  
tel: +39 0376 771777  
fax: +39 0376 772140  
[www.ldr.it](http://www.ldr.it) [info@ldr.it](mailto:info@ldr.it)

Issue: ap ©2009. LDR reserves the right to alter the specification without prior notice.