

## Application

Beam style	variable-spread, soft-edged beam
Suitable for	theatres, TV studios, architectural and commercial applications, worship venues, exhibition halls or stands
Specification level	professional range
Beam angle	11°- 66°
Typical throw distance	2 – 15m

## Electrical specifications

Light source	180W LED, RGBW
Supply Volts	100/260V AC single phase
Frequency / Current	50/60Hz – 0.87A @ 230V AC or 1.8 A @ 110V AC
Power consumption	200W at full power
Cable/connection	1,6m mains cable with fitted Neutrik Power-con IN and OUT, supplied
Standards Compliance	EN60598-2-17, CE marked

## Mechanical specifications

Construction	extruded aluminium and sheet steel
Mounting & suspension	steel stirrup 12mm centre hole + DIN mounting.
Handle	rear
Weight/Packed weight	9,7 kg / 11,9kg
Colour frame	metal, 185 x 185mm, accessory

## Operational specifications

Focus adjustment	screw focus with control at rear
Beam Shaping	using barndoor accessory
DMX channels / connection	6 or 7 ch / XLR5 connectors, IN/OUT
Dimmer module	RGBW
Dimming	from rear panel encoder or remote, 8 or 16 bits, via DMX signal
LED temperature	built-in sensor for real time monitoring
Ambient temperature	35°C max.
Fan speed control	3 modes available: Silent/Auto/ Constant
Fade curve	2 curves (linear, square)
LED Frequency	16KHz- flicker-free
LCD display	Set-up, DMX, monitor,diagnostics
RDM	Integrated

## Optical specifications

Optical system	150mm diameter high-quality borosilicate Fresnel lens
LED array	RGBW, round- shaped, replaceable
Rated LED life	50,000 hours at 25°C, maintains 70% original intensity
Beam colour temperature	Any, from RGBW colour mixing
CRI (Colour Rendering Index)	>90

## Accessories

Metal colour frame	■ 20100106	□ 20100106B	□ 20100106C
4-leaf barndoor	■ 20100306	□ 20100306B	□ 20100306C
Remoto, software uploader	20702072		
Hook clamp	20100900	Safety bond	20101300

## Photometric data


Spot	RGBW								at 1600mA
Beam dia.	0.4	0.8	1.2	1.5	1.9	2.3	2.7	3.1	m
R	3575	892	397	223	143	100	73	56	44,6 lm/W
G	7287	1821	810	455	291	202	149	113	68,7 lm/W
B	9350	2246	1038	584	374	260	190	146	11,8 lm/W
W	9625	2406	1069	601	385	267	197	187	86,2 lm/W
FULL	21450	5362	2383	1341	858	596	437	335	
Distance	2	4	6	8	10	12	14	16	m

Flood									
Beam dia.	2.6	3.9	5.2	6.5	7.8	9.1			m
R	1512	672	378	242	167	124			44,6 lm/W
G	2062	916	513	330	229	168			68,7 lm/W
B	2392	1063	587	382	265	195			11,8 lm/W
W	2255	1002	563	360	250	184			86,2 lm/W
FULL	3987	1772	996	638	443	325			
Distance	2	3	4	5	6	7			m

# arpa f150 RGBW

180W, 100/260VAC, DMX512/RDM  
LED fresnel luminaire

part # ■ 01151200 □ 01151201 □ 01151202



Stylish, compact and extremely high efficiency RGBW led power source Fresnel luminaire, DMX/RDM controllable for 16 bit dimming and infinite colour beams.

Arpa F features a high-quality borosilicate Fresnel lens and perfectly fits in theatrical sets, stages, TV studios, commercial and art displays, schools, worship venues, cruise ships or architectural applications where a bright - colour and evenly distributed soft-edged beam on medium throws is required.

Standard delivery includes 1.6m mains cable with fitted Power-con. All models in the ARPA range are available in 3200K and 5600K white plus RGBW, in a choice of 3 finishes: black, white and silver, and 2 stirrups: manual and pole-operated

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS



Luci della Ribalta srl  
Via Berna 14  
46042 Castel Goffredo (MN), Italy  
tel: +39 0376 771777  
[www.ldr.it](http://www.ldr.it) [info@ldr.it](mailto:info@ldr.it)  
issue: ap ©2023. LDR reserves the right to alter the specification without prior notice.