

Application

Beam style	well-defined, flat field profile projection
Suitable for	medium / large scale theatre
Specification level	professional range
Beam angle	8° - 22°
Typical throw distance	10 – 40m

Electrical specifications

Supply Volts	230/240V AC single phase to ballast unit
Max. Lamp Watts	575W
Lamp base	GX9.5
Auto-disconnect	double-pole microswitch
Cable/connection	2m, multicore cable to ballast, 2m 3x2.5mm ² bare ended cable to power
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Paint/Finish	epoxy powder paint, black or white
Lamp House Construction	extruded aluminium and sheet steel
Ballast	external electromagnetic unit with on/off switch
Reflector	68mm diameter. glass
Optical system	double condenser with variable zoom
Mounting & suspension	steel stirrup with 12mm centre hole and DIN mounting. Spigot for Ø29mm tube supplied
Side Handle	one, covering rear and side of the followspot All handles and controls are thermally insulated
Weight/Packed weight	33 kg / 80,2kg
Packed volume	0,47m ³
Filter cut size	185 x 185mm
Accessory runners	3 slots / accessory
Colour frame	metal, 185 x 185mm, not supplied
Lamp access	lowering base
Lens access	sliding panels beneath lamp tube

Operational specifications

Focus adjustment	slide zoom controls (dia./softness) at side
Lamp alignment	factory set
Beam Shaping	20-leaf iris included; shutters: accessories
Dimming	optical dimmer iris included
Positional adjustment	lever tilt clamp

Lamp types

575W 6000K	Philips MSD 575 GX9.5 3.000 hrs
575W 7200K	Philips MSR 575/2 GX9.5 1.000 hrs

Accessories

Metal colour frame+ front runners	■20109106
5-colour colour changer	■20105106 □20105106B
5-colour colour changer, left handed	■20105105
6-colour colour changer	■20105206
Spare iris diaphragm	20100707 Gobo holder, A/B size 20100807
Black tripod	20102401
Black tripod LEV-LEG	20102400
Spare spigot Ø29mm	20102200
Kit 1-hand control iris/dowser	20107070 Stirrup-kit for suspension 20102900
Flight case with braking wheels	20107180 for f.spot/ballast/col.chang./tripod

Photometric data

Narrow focus										575 MSR
Beam dia.	1.5	1.7	1.9	2.1	2.3	2.5	2.7	2.9	3.1	m
lux	2908	2227	1759	1425	1178	990	843	727	633	
Distance	14	16	18	20	22	24	26	28	30	m

Wide focus

Beam dia.	2.6	3.2	3.7	4.2	4.7	5.3	5.8	6.3	6.8	m
lux	1363	946	695	532	421	341	282	237	202	
Distance	10	12	14	16	18	20	22	24	26	m

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

Canto® 575msd MK2 kit

230V 50/60Hz

discharge followspot

part number : ■ 10857180 □ K10857181



Medium-throw discharge followspot for either MSD or MSR 575 lamp.

Canto® 575 features a large, user-friendly side handle, enhanced mechanics on the dowser and an excellent light output.

A large selection of accessories is available for the Canto range, including a flight case on braking wheels which accepts followspot, fitted colour changer, tripod, ballast unit and lamp

The Canto® 575msd kit includes:

- Canto® 575msd/msr followspot complete with 20-leaf iris, mechanical dimmer, separate ballast unit and spigot.
- Philips 575 MSD lamp
- Black or chrome-plated tripod with adjustable h, 0.9-1.5m
- 5-colour colour changer, fitted
- ATA approved flight-case on braking wheels



Luci della Ribalta srl
Via Berna 14
46042 Castel Goffredo (MN), Italy
tel: +39 0376 771777
www.ldr.it info@ldr.it

issue: ap ©2022. LDR reserves the right to alter the specification without prior notice